Renewable Properties, LLC

879 Sanchez Street San Francisco, CA 94114

www.renewprop.com



PSC SC // L

September 18, 2020

Public Service Commission of South Carolina 101 Executive Center Drive, Suite 100 Columbia, SC 29210

RE: FERC form 556 filing

To Whom It May Concern,

Pursuant to 18 C.F.R. 292.207(c), attached please find a copy of the Qualifying Facility self-certification for RPSC Solar 3, LLC (Berry Road Solar Project) that was filed with FERC on August 30, 2020. A soft copy of the filing was sent via email.

Please do not hesitate to reach out with any questions/comments. I appreciate your time and consideration.

I look forward to hearing from you.

Sincerely,

RENEWABLE PROPERTIES

Aaron Halimi President 530-518-7669 aaron@renewprop.com

Information Required for Cogeneration Facility

If you indicated in line 1k that you are seeking qualifying cogeneration facility status for your facility, then you must respond to the items on pages 11 through 13. Otherwise, skip pages 11 through 13.

10 4141	cillo on pages in allough	12. Calcimitation programme and programme an		
	energy (such as heat or suse of energy. Pursuant cycle cogeneration facilithermal application or p	92.202(c), a cogeneration facility produces electric energy and forms of useful thermal steam) used for industrial, commercial, heating, or cooling purposes, through the sequential to 18 C.F.R. § 292.202(s), "sequential use" of energy means the following: (1) for a toppingty, the use of reject heat from a power production process in sufficient amounts in a rocess to conform to the requirements of the operating standard contained in 18 C.F.R. § ottoming-cycle cogeneration facility, the use of at least some reject heat from a thermal or power production.		
	10a What type(s) of cog	eneration technology does the facility represent? (check all that apply)		
	☐ Topping-cycle	cogeneration Bottoming-cycle cogeneration		
	10b To help demonstrate the sequential operation of the cogeneration process, and to support compliance with other requirements such as the operating and efficiency standards, include with your filing a mass and heat balance diagram depicting average annual operating conditions. This diagram must include certain items and meet certain requirements, as described below. You must check next to the description of each requirement below to certify that you have complied with these requirements.			
	Check to certify			
	compliance with indicated requirement	Requirement		
ation		Diagram must show orientation within system piping and/or ducts of all prime movers, heat recovery steam generators, boilers, electric generators, and condensers (as applicable), as well as any other primary equipment relevant to the cogeneration process.		
gener		Any average annual values required to be reported in lines 10b, 12a, 13a, 13b, 13d, 13f, 14a, 15b, 15d and/or 15f must be computed over the anticipated hours of operation.		
General Cogeneration Information		Diagram must specify all fuel inputs by fuel type and average annual rate in Btu/h. Fuel for supplementary firing should be specified separately and clearly labeled. All specifications of fuel inputs should use lower heating values.		
ene		Diagram must specify average gross electric output in kW or MW for each generator.		
5		Diagram must specify average mechanical output (that is, any mechanical energy taken off of the shaft of the prime movers for purposes not directly related to electric power generation) in horsepower, if any. Typically, a cogeneration facility has no mechanical output.		
		At each point for which working fluid flow conditions are required to be specified (see below), such flow condition data must include mass flow rate (in lb/h or kg/s), temperature (in °F, R, °C or K), absolute pressure (in psia or kPa) and enthalpy (in Btu/lb or kJ/kg). Exception: For systems where the working fluid is <i>liquid only</i> (no vapor at any point in the cycle) and where the type of liquid and specific heat of that liquid are clearly indicated on the diagram or in the Miscellaneous section starting on page 19, only mass flow rate and temperature (not pressure and enthalpy) need be specified. For reference, specific heat at standard conditions for pure liquid water is approximately 1.002 Btu/(lb*R) or 4.195 kJ/(kg*K).		
		Diagram must specify working fluid flow conditions at input to and output from each steam turbine or other expansion turbine or back-pressure turbine.		
		Diagram must specify working fluid flow conditions at delivery to and return from each thermal application.		
		Diagram must specify working fluid flow conditions at make-up water inputs.		

	EPAct 2005 cogeneration facilities: The Energy Policy Act of 2005 (EPAct 2005) established a new section 210(n) of the Public Utility Regulatory Policies Act of 1978 (PURPA), 16 USC 824a-3(n), with additional requirements for any qualifying cogeneration facility that (1) is seeking to sell electric energy pursuant to section 210 of PURPA and (2) was either not a cogeneration facility on August 8, 2005, or had not filed a self-certification or application for Commission certification of QF status on or before February 1, 2006. These requirements were implemented by the Commission in 18 C.F.R. § 292.205(d). Complete the lines below, carefully following the instructions, to demonstrate whether these additional requirements apply to your cogeneration facility and, if so, whether your facility complies with such requirements.
	11a Was your facility operating as a qualifying cogeneration facility on or before August 8, 2005? Yes No
	11b Was the initial filing seeking certification of your facility (whether a notice of self-certification or an application for Commission certification) filed on or before February 1, 2006? Yes No
ae	If the answer to either line 11a or 11b is Yes, then continue at line 11c below. Otherwise, if the answers to both lines 11a and 11b are No, skip to line 11e below.
EPAct 2005 Requirements for Fundamental Use of Energy Output from Cogeneration Facilities	11c With respect to the design and operation of the facility, have any changes been implemented on or after February 2, 2006 that affect general plant operation, affect use of thermal output, and/or increase net power production capacity from the plant's capacity on February 1, 2006?
me n F	Yes (continue at line 11d below)
Fundai ieratio	No. Your facility is not subject to the requirements of 18 C.F.R. § 292.205(d) at this time. However, it may be subject to to these requirements in the future if changes are made to the facility. At such time, the applicant would need to recertify the facility to determine eligibility. Skip lines 11d through 11j.
for	11d Does the applicant contend that the changes identified in line 11c are not so significant as to make the facility a "new" cogeneration facility that would be subject to the 18 C.F.R. § 292.205(d) cogeneration requirements?
ements rom C	Yes. Provide in the Miscellaneous section starting on page 19 a description of any relevant changes made to the facility (including the purpose of the changes) and a discussion of why the facility should not be considered a "new" cogeneration facility in light of these changes. Skip lines 11e through 11j.
Require	No. Applicant stipulates to the fact that it is a "new" cogeneration facility (for purposes of determining the applicability of the requirements of 18 C.F.R. § 292.205(d)) by virtue of modifications to the facility that were initiated on or after February 2, 2006. Continue below at line 11e.
)5 F VO	11e Will electric energy from the facility be sold pursuant to section 210 of PURPA?
t 20(nerg	Yes. The facility is an EPAct 2005 cogeneration facility. You must demonstrate compliance with 18 C.F.R. § 292.205(d)(2) by continuing at line 11f below.
EPAc of Ei	No. Applicant certifies that energy will <i>not</i> be sold pursuant to section 210 of PURPA. Applicant also certifies its understanding that it must recertify its facility in order to determine compliance with the requirements of 18 C.F.R. § 292.205(d) <i>before</i> selling energy pursuant to section 210 of PURPA in the future. Skip lines 11f through 11j.
-	11f 1s the net power production capacity of your cogeneration facility, as indicated in line 7g above, less than or equal to 5,000 kW?
	Yes, the net power production capacity is less than or equal to 5,000 kW. 18 C.F.R. § 292.205(d)(4) provides a rebuttable presumption that cogeneration facilities of 5,000 kW and smaller capacity comply with the requirements for fundamental use of the facility's energy output in 18 C.F.R. § 292.205(d)(2). Applicant certifies its understanding that, should the power production capacity of the facility increase above 5,000 kW, then the facility must be recertified to (among other things) demonstrate compliance with 18 C.F.R. § 292.205(d)(2). Skip lines 11g through 11j.
	No, the net power production capacity is greater than 5,000 kW. Demonstrate compliance with the requirements for fundamental use of the facility's energy output in 18 C.F.R. § 292.205(d)(2) by continuing on the next page at line 11g.

Energy Output from Cogeneration Facilities (continued)

EPAct 2005 Requirements for Fundamental Use

Lines 11g through 11k below guide the applicant through the process of demonstrating compliance with the requirements for "fundamental use" of the facility's energy output. 18 C.F.R. § 292.205(d)(2). Only respond to the lines on this page if the instructions on the previous page direct you to do so. Otherwise, skip this page.

18 C.F.R. § 292.205(d)(2) requires that the electrical, thermal, chemical and mechanical output of an EPAct 2005 cogeneration facility is used fundamentally for industrial, commercial, residential or institutional purposes and is not intended fundamentally for sale to an electric utility, taking into account technological, efficiency, economic, and variable thermal energy requirements, as well as state laws applicable to sales of electric energy from a qualifying facility to its host facility. If you were directed on the previous page to respond to the items on this page, then your facility is an EPAct 2005 cogeneration facility that is subject to this "fundamental use" requirement.

The Commission's regulations provide a two-pronged approach to demonstrating compliance with the requirements for fundamental use of the facility's energy output. First, the Commission has established in 18 C.F.R. § 292.205(d)(3) a "fundamental use test" that can be used to demonstrate compliance with 18 C.F.R. § 292.205(d)(2). Under the fundamental use test, a facility is considered to comply with 18 C.F.R. § 292.205(d)(2) if at least 50 percent of the facility's total annual energy output (including electrical, thermal, chemical and mechanical energy output) is used for industrial, commercial, residential or institutional purposes.

Second, an applicant for a facility that does not pass the fundamental use test may provide a narrative explanation of and support for its contention that the facility nonetheless meets the requirement that the electrical, thermal, chemical and mechanical output of an EPAct 2005 cogeneration facility is used fundamentally for industrial, commercial, residential or institutional purposes and is not intended fundamentally for sale to an electric utility, taking into account technological, efficiency, economic, and variable thermal energy requirements, as well as state laws applicable to sales of electric energy from a qualifying facility to its host facility.

Complete lines 11g through 11i below to determine compliance with the fundamental use test in 18 C.F.R. § 292.205(d)(3). Complete lines 11g through 11j even if you do not intend to rely upon the fundamental use test to demonstrate compliance with 18 C.F.R. § 292.205(d)(2).

11g Amount of electrical, thermal, chemical and mechanical energy output (net of internal	
generation plant losses and parasitic loads) expected to be used annually for industrial,	
commercial, residential or institutional purposes and not sold to an electric utility	MWh
11h Total amount of electrical, thermal, chemical and mechanical energy expected to be	
sold to an electric utility	MWh
11i Percentage of total annual energy output expected to be used for industrial,	
commercial, residential or institutional purposes and not sold to a utility	
= 100 * 11g /(11g + 11h)	с %

11j is the response in line 11i greater than or equal to 50 percent?

Yes. Your facility complies with 18 C.F.R. § 292.205(d)(2) by virtue of passing the fundamental use test provided in 18 C.F.R. § 292.205(d)(3). Applicant certifies its understanding that, if it is to rely upon passing the fundamental use test as a basis for complying with 18 C.F.R. § 292.205(d)(2), then the facility must comply with the fundamental use test both in the 12-month period beginning with the date the facility first produces electric energy, and in all subsequent calendar years.

No. Your facility does not pass the fundamental use test. Instead, you must provide in the Miscellaneous section starting on page 19 a narrative explanation of and support for why your facility meets the requirement that the electrical, thermal, chemical and mechanical output of an EPAct 2005 cogeneration facility is used fundamentally for industrial, commercial, residential or institutional purposes and is not intended fundamentally for sale to an electric utility, taking into account technological, efficiency, economic, and variable thermal energy requirements, as well as state laws applicable to sales of electric energy from a QF to its host facility. Applicants providing a narrative explanation of why their facility should be found to comply with 18 C.F.R. § 292.205(d)(2) in spite of non-compliance with the fundamental use test may want to review paragraphs 47 through 61 of Order No. 671 (accessible from the Commission's QF website at www.ferc.gov/QF), which provide discussion of the facts and circumstances that may support their

explanation. Applicant should also note that the percentage reported above will establish the standard that that facility must comply with, both for the 12-month period beginning with the date the facility first produces electric energy, and in all subsequent calendar years. See Order No. 671 at paragraph 51. As such, the applicant should make sure that it reports appropriate values on lines 11g and 11h above to serve as the relevant annual standard, taking into account expected variations in production conditions.



ACCEPTED FOR PROCESSING - 2020 October 6 7:40 AM - SCPSC - ND-2020-35-E - Page 5 of 10

Information Required for Topping-Cycle Cogeneration Facility

If you indicated in line 10a that your facility represents topping-cycle cogeneration technology, then you must respond to

the items on pages 14 and 15. Otherwise, skip pages 14 and 15. The thermal energy output of a topping-cycle cogeneration facility is the net energy made available to an industrial or commercial process or used in a heating or cooling application. Pursuant to sections 292.202(c), (d) and (h) of the Commission's regulations (18 C.F.R. §§ 292.202(c), (d) and (h)), the thermal energy output of a qualifying toppingcycle cogeneration facility must be useful. In connection with this requirement, describe the thermal output of the topping-cycle cogeneration facility by responding to lines 12a and 12b below. 12a Identify and describe each thermal host, and specify the annual average rate of thermal output made available to each host for each use. For hosts with multiple uses of thermal output, provide the data for each use in separate rows. Average annual rate of thermal output attributable to use (net of Name of entity (thermal host) Thermal host's relationship to facility; heat contained in process taking thermal output Thermal host's use of thermal output return or make-up water) Select thermal host's relationship to facility 1) Select thermal host's use of thermal output Btu/h Select thermal host's relationship to facility 2) **Usefulness of Topping-Cycle** Select thermal host's use of thermal output Btu/h Select thermal host's relationship to facility 3) Select thermal host's use of thermal output Btu/h **Thermal Output** Select thermal host's relationship to facility 4) Select thermal host's use of thermal output Btu/h Select thermal host's relationship to facility 5) Select thermal host's use of thermal output Btu/h Select thermal host's relationship to facility 6) Select thermal host's use of thermal output Btu/h Check here and continue in the Miscellaneous section starting on page 19 if additional space is needed 12b Demonstration of usefulness of thermal output: At a minimum, provide a brief description of each use of the thermal output identified above. In some cases, this brief description is sufficient to demonstrate usefulness. However, if your facility's use of thermal output is not common, and/or if the usefulness of such thermal output is not reasonably clear, then you must provide additional details as necessary to demonstrate usefulness. Your application may be rejected and/or additional information may be required if an insufficient showing of usefulness is made. (Exception: If you have previously received a Commission certification approving a specific use of thermal output related to the instant facility, then you need only provide a brief description of that use and a reference by date and docket number to the order certifying your facility with the indicated use. Such exemption may not be used if any change creates a material deviation from the previously authorized use.) If additional space is needed, continue in the Miscellaneous section starting on page 19.

Applicants for facilities representing topping-cycle technology must demonstrate compliance with the topping-cycle operating standard and, if applicable, efficiency standard. Section 292.205(a)(1) of the Commission's regulations (18 C.F.R. § 292.205(a)(1)) establishes the operating standard for topping-cycle cogeneration facilities: the useful thermal energy output must be no less than 5 percent of the total energy output. Section 292.205(a)(2) (18 C.F.R. § 292.205(a)(2)) establishes the efficiency standard for topping-cycle cogeneration facilities for which installation commenced on or after March 13, 1980: the useful power output of the facility plus one-half the useful thermal energy output must (A) be no less than 42.5 percent of the total energy input of natural gas and oil to the facility; and (B) if the useful thermal energy output is less than 15 percent of the total energy output of the facility, be no less than 45 percent of the total energy input of natural gas and oil to the facility. To demonstrate compliance with the topping-cycle operating and/or efficiency standards, or to demonstrate that your facility is exempt from the efficiency standard based on the date that installation commenced, respond to lines 13a through 13l below.

If you indicated in line 10a that your facility represents both topping-cycle and bottoming-cycle cogeneration technology, then respond to lines 13a through 13I below considering only the energy inputs and outputs attributable to the topping-cycle portion of your facility. Your mass and heat balance diagram must make clear which mass and energy flow values and system components are for which portion (topping or bottoming) of the cogeneration system.

cogeneration system.		
13a Indicate the annual average rate of useful thermal energy output made available		
to the host(s), net of any heat contained in condensate return or make-up water		Btu/h
13b Indicate the annual average rate of net electrical energy output		kW
13c Multiply line 13b by 3,412 to convert from kW to Btu/h	0	Btu/h
13d Indicate the annual average rate of mechanical energy output taken directly off of the shaft of a prime mover for purposes not directly related to power production (this value is usually zero)		hp
13e Multiply line 13d by 2,544 to convert from hp to Btu/h	0	Btu/h
13f Indicate the annual average rate of energy input from natural gas and oil		Btu/h
13g Topping-cycle operating value = 100 * 13a / (13a + 13c + 13e)	0	%
13h Topping-cycle efficiency value = 100 * (0.5*13a + 13c + 13e) / 13f	0	%
13i Compliance with operating standard: Is the operating value shown in line 13g gre	ater than or equal to 59	%?

Compliance with operating standard. Is the opera	rang value shown in line 15g greater than or equal to \$70
Yes (complies with operating standard)	No (does not comply with operating standard)

13j	Did installation of the facility in its current form commence on or after March	13,	1980?
-----	---------------------------------------------------------------------------------	-----	-------

Yes. Your facility is subject to the efficiency requirements of 18 C.F.R. § 292.205(a)(2). Demonstrate compliance with the efficiency requirement by responding to line 13k or 13l, as applicable, below.
compliance with the emeterly requirement by responding to line 15 to 15

No.	Your facility is exempt from the efficiency standard.	Skip lines	13k and	13l
-----	-------------------------------------------------------	------------	---------	-----

Yes (complies with efficiency standard)

13k Compliance with efficiency standard (for low operating value): If the operating value shown in line 13g is less than 15%, then indicate below whether the efficiency value shown in line 13h greater than or equal to 45%:

No (does not comply with efficiency standard)

131 Compliance with efficiency standard (for high operating value): If the operating value shown in line 13g is
greater than or equal to 15%, then indicate below whether the efficiency value shown in line 13h is greater than or
equal to 42.5%:

1	Yes (complies with efficiency standard)	No (does not comply with efficiency standard)
1	1 1 tes (complies with efficiency standard)	110 (does not comply with emerging standard)









Information Required for Bottoming-Cycle Cogeneration Facility

If you indicated in line 10a that your facility represents bottoming-cycle cogeneration technology, then you must respond

to the ite	ems (on pages 16 and 17. Otherwise, sl	rip pages 16 and 17.	~~~		
	The thermal energy output of a bottoming-cycle cogeneration facility is the energy related to the process(es) from which at least some of the reject heat is then used for power production. Pursuant to sections 292.202(c) and (e) of the Commission's regulations (18 C.F.R. § 292.202(c) and (e)), the thermal energy output of a qualifying bottoming-cycle cogeneration facility must be useful. In connection with this requirement, describe the process(es) from which at least some of the reject heat is used for power production by responding to lines 14a and 14b below.					
	14a Identify and describe each thermal host and each bottoming-cycle cogeneration process engaged in by each host. For hosts with multiple bottoming-cycle cogeneration processes, provide the data for each process in					
		Name of entity (thermal host) performing the process from which at least some of the reject heat is used for power production	Thermal host's relationship to facility; Thermal host's process type	Has the energy input to the thermal host been augmented for purposes of increasing power production capacity? (if Yes, describe on p. 19)		
	1)		Select thermal host's relationship to facility	Yes No		
	''		Select thermal host's process type			
<u>е</u>	2)		Select thermal host's relationship to facility	Yes 🔲 No 🗌		
, , ,			Select thermal host's process type			
g-(3)		Select thermal host's relationship to facility	Yes 🔲 No 🗌		
in Xt	لـــــــــا		Select thermal host's process type			
on utp		Check here and continue in the	ne Miscellaneous section starting on page 19 if addit	ional space is needed		
Usefulness of Bottoming-Cycle Thermal Output	idei faci mu: add prei faci to t cha	ntified above. In some cases, this lity's process is not common, and/ st provide additional details as nec litional information may be require viously received a Commission cellity, then you need only provide a he order certifying your facility with	thermal output: At a minimum, provide a brief description is sufficient to demonstrate useful for if the usefulness of such thermal output is not recessary to demonstrate usefulness. Your application ed if an insufficient showing of usefulness is made. rtification approving a specific bottoming-cycle probrief description of that process and a reference by the the indicated process. Such exemption may not ade.) If additional space is needed, continue in the Made.	ness. However, if your asonably clear, then you in may be rejected and/or (Exception: If you have cess related to the instant date and docket number be used if any material		

No (does not comply with efficiency standard)

Bottoming-Cycle Operating and Efficiency Value Calculation

Applicants for facilities representing bottoming-cycle technology and for which installated March 13, 1990 must demonstrate compliance with the bottoming-cycle efficiency start the Commission's regulations (18 C.F.R. § 292.205(b)) establishes the efficiency standard cogeneration facilities: the useful power output of the facility must be no less than 45 point for supplementary firing. To demonstrate compliance with the bestandard (if applicable), or to demonstrate that your facility is exempt from this standard installation of the facility began, respond to lines 15a through 15h below.	ndards. Section 292.205(b) of d for bottoming-cycle percent of the energy input ottoming-cycle efficiency	
f you indicated in line 10a that your facility represents <i>both</i> topping-cycle and bottoming-cycle cogeneration echnology, then respond to lines 15a through 15h below considering only the energy inputs and outputs ttributable to the bottoming-cycle portion of your facility. Your mass and heat balance diagram must make clear which mass and energy flow values and system components are for which portion of the cogeneration system topping or bottoming).		
15a Did installation of the facility in its current form commence on or after March 13, 1	980?	
Yes. Your facility is subject to the efficiency requirement of 18 C.F.R. § 292.205(b). Demonstrative with the efficiency requirement by responding to lines 15b through 15h below.		
☐ No. Your facility is exempt from the efficiency standard. Skip the rest of page 1	7.	
15b Indicate the annual average rate of net electrical energy output	kW	
15c Multiply line 15b by 3,412 to convert from kW to Btu/h	0 Btu/h	
15d Indicate the annual average rate of mechanical energy output taken directly off of the shaft of a prime mover for purposes not directly related to power production		
(this value is usually zero)	hp	

15e Multiply line 15d by 2,544 to convert from hp to Btu/h

15g Bottoming-cycle efficiency value = 100 * (15c + 15e) / 15f


Yes (complies with efficiency standard)

than or equal to 45%:

15f Indicate the annual average rate of supplementary energy input from natural gas



0 Btu/h





Certificate of Completeness, Accuracy and Authority

Applicant must certify compliance with and understanding of filing requirements by checking next to each item below and signing at the bottom of this section. Forms with incomplete Certificates of Completeness, Accuracy and Authority will be

rejected by the Secretary of the Commission	on.	
Signer identified below certifies the follow	ing: (check all items and applicable subitems)	
He or she has read the filing, including mass and heat balance diagrams, and knows its contents.	g any information contained in any attached docun any information contained in the Miscellaneous se	nents, such as cogeneration ection starting on page 19, and
He or she has provided all of the required information for certification, and the provided information is true as stated, to the best of his or her knowledge and belief.		
He or she possess full power and authority to sign the filing; as required by Rule 2005(a)(3) of the Commission's Rules of Practice and Procedure (18 C.F.R. § 385.2005(a)(3)), he or she is one of the following: (check one)		
☐ The person on whose behalf the filing is made		
An officer of the corporation, trust, association, or other organized group on behalf of which the filing is made		
An officer, agent, or employe of the governmental authority, agency, or instrumentality on behalf of which the filing is made		
A representative qualified to practice before the Commission under Rule 2101 of the Commission's Rules of Practice and Procedure (18 C.F.R. § 385.2101) and who possesses authority to sign		
He or she has reviewed all automatic calculations and agrees with their results, unless otherwise noted in the Miscellaneous section starting on page 19.		
He or she has provided a copy of this Form 556 and all attachments to the utilities with which the facility will interconnect and transact (see lines 4a through 4d), as well as to the regulatory authorities of the states in which the facility and those utilities reside. See the Required Notice to Public Utilities and State Regulatory Authorities section on page 3 for more information.		
Provide your signature, address and signature date below. Rule 2005(c) of the Commission's Rules of Practice and Procedure (18 C.F.R. § 385.2005(c)) provides that persons filing their documents electronically may use typed characters representing his or her name to sign the filed documents. A person filing this document electronically should sign (by typing his or her name) in the space provided below.		
Your Signature	Your address	Date
	879 Sanchez Street, San Francisco	
Aaron Halimi	CA 94114	8/30/2020
Audit Notes		
Commission Staff Use Only:		

FERC Form 556 Page 19 - All Facilities

Miscellaneous

Use this space to provide any information for which there was not sufficient space in the previous sections of the form to provide. For each such item of information *clearly identify the line number that the information belongs to*. You may also use this space to provide any additional information you believe is relevant to the certification of your facility.

Your response below is not limited to one page. Additional page(s) will automatically be inserted into this form if the length of your response exceeds the space on this page. Use as many pages as you require.

Change of applicant address from "2914 Larkin Street, San Francisco, CA 94109" to "879 Sanchez Street, San Francisco, CA 94114" (1a-le)

Change of direct ownership from "Renewable Properties, LLC" to "RenewProp Lessor 4, LLC" (5a)

Change of indirect ownership from "none" to "RenewProp MM 4, LLC", "Blockchain Renewables, LLC", "Renewable Properties Holdings, LLC" and "Renewable Properties, LLC" (5b)

Change (7a) to 2,809.2 kW and (7d) to 809.2 kW.